

Pipe ring	Picture	Applications						Technical Data			Features		Approvals						
		Fresh water distribution pipes	Heating pipes	Gas distribution pipes	Waste water distribution pipes	Light industrial applications	Corrosive surroundings	Recommended static load for suspended installation - F _{rec}	Average noise reduction (ΔL)	Temperature resistance	Clamping range	Connection boss	Special features	Building material class B2	Acoustic insulation DIN 4109	Fire resistance	Shock approval	Dynamic approval	RAL approval

Light-duty galvanized pipe rings

MP-LHI M8		●	●	●				200 N to 750 N	17 dB(A)	-40°C to +110°C	8 – 66 mm	M8	<ul style="list-style-type: none"> One clamping screw Securely fixed rubber inlay Short connection boss 	●	●				●
MP-HI M8/M10		●	●	●	●			600 N to 1500 N	17 dB(A)	-40°C to +110°C	8 – 172 mm	M8/M10	<ul style="list-style-type: none"> Securely fixed rubber inlay Safe closure with click feedback Double connection boss 	●	●				●
MP-H M8/M10		●	●	●				600 N to 1500 N			16 – 172 mm	M8/M10	<ul style="list-style-type: none"> Safe closure with click feedback Double connection boss 						

Medium-duty galvanized pipe rings

MPN-RC		●	●	●	●			1000 N to 2500 N	15 dB(A)	-50°C to +120°C	8 – 170 mm	M8/M10	<ul style="list-style-type: none"> Innovative low-friction strip for easy pipe positioning Three-stage quick closure One clamping screw 	●	●				
MPN-S		●	●	●				1000 N to 2500 N			15 – 170 mm	M8/M10	<ul style="list-style-type: none"> Three-stage quick closure One clamping screw 						
MPN-SI		●	●	●	●			1000 N to 2500 N	18 dB(A)	-50°C to +120°C	10 – 170 mm	M8/M10/1/2"	<ul style="list-style-type: none"> Three-stage quick closure One clamping screw 	●	●				
MPN-GK/-G		●			●			1000 N to 1500 N	17 dB(A) / 19 dB(A)	-50°C to +110°C	16 – 160 mm	M8 and M8/M10	<ul style="list-style-type: none"> Three-stage quick closure One clamping screw Special velour-like finish for low friction to allow movement of the pipe 	●	●				
MPN-QRC		●	●	●	●			1000 N to 2500 N	16 dB(A)	-50°C to +120°C	8 – 118 mm	M8 or M10	<ul style="list-style-type: none"> Innovative low-friction strip for easy pipe positioning Three-stage quick closure One clamping screw Push connection, no twisting 	●	●	●			

Heavy-duty galvanized pipe rings

MP-MI		●	●	●	●	●		3000 N to 5000 N	18 dB(A)	-50°C to +120°C	15 – 250 mm	M10/M12, M16, 1/2", 3/4"	<ul style="list-style-type: none"> Solidly made, strong and rigid Welded clamping nuts Civil protection approval 	●	●	●	●		
MP-M		●	●	●		●		3000 N to 5000 N			15 – 224 mm	M16, 1/2", 3/4"	<ul style="list-style-type: none"> Solidly made, strong and rigid Welded clamping nuts Civil protection approval 				●		
MP-MXI		●	●	●	●	●		6000 N to 17000 N	16 dB(A)	-50°C to +120°C	60 – 508 mm	M10/M12, M16, 3/4", 1"	<ul style="list-style-type: none"> Highest loads up to 17kN Dynamic load tested 	●	●	●	●	●	
MP-MX		●	●	●		●		4000 N to 17000 N			60 – 508 mm	M10/M12, M16, 3/4", 1"	<ul style="list-style-type: none"> Highest loads up to 17kN Dynamic load tested 				●	●	●
MP-MIS		●	●	●	●	●		3000 N to 5000 N		-60°C to +200°C	15 – 250 mm	M10/M12, M16	<ul style="list-style-type: none"> Silicon inlay High temperature resistance until +200°C 	●		●			

Hot-dip galvanized pipe rings

MP-MI-F		●	●	●	●	●		3000 N	18 dB(A)	-50°C to +120°C	20 – 90 mm	M10	<ul style="list-style-type: none"> Good resistance to corrosion (45 µm) High loads 	●	●	●			
MP-M-F		●	●	●		●		3000 N			20 – 90 mm	M10	<ul style="list-style-type: none"> Good resistance to corrosion (45 µm) High loads 				●		
MP-MXI-F		●	●	●	●	●		6000 N to 17000 N	16 dB(A)	-50°C to +120°C	60 – 508 mm	M10/M12, M16, 3/4", 1"	<ul style="list-style-type: none"> Good resistance to corrosion (45 µm) High loads 	●	●	●		●	
MP-MX-F		●	●	●		●		6000 N to 17000 N			60 – 508 mm	M10/M12, M16, 3/4", 1"	<ul style="list-style-type: none"> Good resistance to corrosion (45 µm) High loads 				●		●

Stainless steel pipe rings

MP-SRNI		●	●	●	●	●		1500 N	15 dB(A)	-50°C to +120°C	15.5 – 64 mm	M8, M10	<ul style="list-style-type: none"> High quality (A5) 	●	●	●			
MP-SRN		●	●	●		●		900 N			15.5 – 64.5 mm	M8, M10	<ul style="list-style-type: none"> High quality (A5) 				●		●
MP-MRI		●	●	●	●	●		3000 N to 5000 N	18 dB(A)	-50°C to +120°C	68 – 224 mm	M10, M12, M16	<ul style="list-style-type: none"> High quality (A5) 	●	●	●			
MP-MR		●	●	●		●		4000 N to 6000 N			68 – 224 mm	M10, M12, M16	<ul style="list-style-type: none"> High quality (A5) 				●		●
MP-MRXI		●	●	●	●	●		10000 N to 13000 N	16 dB(A)	-50°C to +120°C	244 – 508 mm	M16	<ul style="list-style-type: none"> High quality (A5) 	●	●	●			