

Wood Framing

Technology	Ideally suited for						Fastener
	Wall framing	Sheeting	Roof framing	Roof paneling	Cavity battens	Trim, cladding, fencing, decking	

Dry indoor service



GX-WF	●		●				GX-WF smooth bright
	●		●				GX-WF profiled bright

Mostly dry indoor service



GX-WF		●		●	●		GX-WF smooth galvanized
		●		●	●		GX-WF profiled galvanized

Fastener	Description	Approvals	Page
----------	-------------	-----------	------

	D-head style No coating (bright nail) Smooth shank	●	269
	No coating (bright nail) Profiled shank for increased pull-out resistance	●	269

	D-head style Zinc galvanized nail (12 µm) Smooth shank	●	269
	D-head style Zinc galvanized nail (12 µm) Profiled shank for increased pull-out resistance	●	269

Wood Framing







Technology	Ideally suited for						Fastener
	Wall framing	Sheeting	Roof framing	Roof paneling	Cavity battens	Trim, cladding, fencing, decking	

Outdoor service



GX-WF							
	●						GX-WF smooth HDG
	●						GX-WF profiled HDG
	●						GX-WF stainless clipped head A2
	●						GX-WF stainless full round head A2
	●						GX-WF stainless clipped head A4
	●						GX-WF stainless full round head A4

Fastener	Description	Approvals	Page
----------	-------------	-----------	------

	D-head style Hot dip galvanized nail (55 µm) Smooth shank	●	269
	D-head style Hot dip galvanized nail (55 µm) Profiled shank for increased pull-out resistance	●	269
	D-head style A2 Stainless steel nail Profiled shank for increased pull-out resistance	●	269
	Full round head style A2 Stainless steel nail Profiled shank for increased pull-out resistance	●	269
	D-head style A4 Stainless steel nail Profiled shank for increased pull-out resistance	●	269
	Full round head style A4 Stainless steel nail Profiled shank for increased pull-out resistance	●	269

