

Safety data sheet

according to 1907/2006/EC, Article 31 / ISO 11014

Printing date 28.11.2012 Version number 6 Revision: 28.11.2012

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Hilti HIT-HY20
- · Container size 330 ml, 500 ml, 1400 ml
- \cdot Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use Building and construction work
- · Application of the substance / the preparation Adhesive mortar for anchor fastenings in hollow masonry
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Hilti Ireland, 1850 287 387.

Unit C4, North City Business Park,

Finglas, Dublin 11, Ireland

Phone: 1850 287 387 Fax: 1800 654 600 Email: iesales@hilti.com

· Informing department:

anchor.hse@hilti.com

see section 16

· Emergency telephone number:

Schweizerisches Toxikologisches Informationszentrum - 24 h Service

Tel.: 0041 / 44 251 51 51 (international)

Hilti Ireland,

Phone: 1850 287 387 Fax: 1800 654 600

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Sensitising

R43: May cause sensitisation by skin contact.



O; Oxidising

R7: May cause fire.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

· Label elements

· Labelling according to EU guidelines:

The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (GefStoffV)

 \cdot Code letter and hazard designation of product:





Xi Irritant O Oxidising

· Hazard-determining components of labelling:

dibenzoyl peroxide

methacrylic acid, monoester with propane-1,2-diol

- · Risk phrases:
- 7 May cause fire.
- 43 May cause sensitisation by skin contact.
- · Safety phrases:
- 3 Keep in a cool place.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of water and soap.
- 37/39 Wear suitable gloves and eye/face protection.

· Special labelling of certain preparations:

Restricted to professional users.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 2)

(Contd. of page 1)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.11.2012 Version number 6 Revision: 28.11.2012

/ ISO 11014

Trade name: Hilti HIT-HY20

· vPvB: Not applicable.

· Additional information:



- · Information pertaining to particular dangers for man and environment: A None
- · Information pertaining to particular dangers for man and environment: B
- R 43 May cause sensitisation by skin contact

R 7 May cause fire

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

2-Component-foilpack, contains:

Component A: Urethane methacrylate resin, inorganic filler

Component B: Dibenzoyl peroxide, phlegmatized

Mixture of the substances listed below with harmless additions.

· Dangerous compone	ents:	
CAS: 94-36-0	dibenzoyl peroxide	5-15%
EINECS: 202-327-6	X i R36; X xi R43; M E R3;	
	♦ 🚱 Org. Perox. B, H241; 🗘 Eye Irrit. 2, H319; Skin Sens. 1, H317	

· Dangerous components A: None

 • Dangerous components B:

 CAS: 94-36-0
 dibenzoyl peroxide

 EINECS: 202-327-6
 dibenzoyl peroxide

 Xi R36;
 Xi R43;

 Xi R43;
 E R3;

 O R7

 Org. Perox. B, H241;
 Eye Irrit. 2, H319; Skin Sens. 1, H317

- · SVHC None
- · Additional information For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation

Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Move to fresh air in case of accidental inhalation of vapours. Consult a doctor after significant exposure.

- · After skin contact Instantly wash with water and soap and rinse thoroughly. If skin irritation persist, call a physician.
- $\cdot \ After \ eye \ contact$

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Call a doctor immediately.

· After swallowing

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

- · Information for doctor
- · Most important symptoms and effects, both acute and delayed Allergic reactions
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fire with alcohol-resistant foam.
- · Special hazards arising from the substance or mixture

Can be released in case of fire

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

- Under certain fire conditions, traces of other toxic gases cannot be excluded.
- · Advice for firefighters
- **Protective equipment:** In the event of fire, wear self contained breathing apparatus

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Keep away from ignition sources

(Contd. on page 3)



Safety data sheet ccording to 1907/2006/EC, Article 31 / ISO 11014

Version number 6 Revision: 28.11.2012 Printing date 28.11.2012

Trade name: Hilti HIT-HY20

(Contd. of page 2)

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

- Environmental precautions: Do not allow to enter drainage system, surface or ground water.
- · Methods and material for containment and cleaning up:

Collect mechanically.

Dispose of contaminated material as waste according to item 13.

Reference to other sections

See Section 8 for information on personal protection equipment.

7 Handling and storage

- · Handling
- · Precautions for safe handling

Check the expiry date: see imprint on manifold (month/year). Do not use expired mortar!

The usual precautionary measures should be adhered to general rules for handling chemicals.

Keep away from heat and direct sunlight.

- · Information about protection against explosions and fires: Keep ignition sources away Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and containers: Keep in a cool, dry and dark place; 5 °C to 25 °C.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · Storage class

As per VCI (1991) storage classification concept.

· Specific end use(s) Adhesive mortar for anchor fastenings in hollow masonry

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

The product has a pasty consistency. Exposure limit values for respirable dusts ar not relevant for this product.

- · Additional information: The lists that were valid during the compilation were used as basis.
- · Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to general rules for handling chemicals.

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Be sure to clean skin thoroughly after work and before breaks.

Take off immediately all contaminated clothing

Avoid contact with the eyes and skin.

Keep away from foodstuffs, beverages and food.

- · Breathing equipment: Not required.
- Protection of hands:

Protective gloves

EN 374 / EN 388

Avoid direct contact with the chemical/ the product/ the preparation by organizational measures.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not suitable are gloves made of the following materials:

Natural rubber, NR

Leather gloves

Strong gloves

Eye protection:

Tightly sealed safety glasses.

EN 166 / EN 170

· Body protection: Protective work clothing.

9 Physical and chemical properties

- Information on basic physical and chemical properties
- **General Information**
- · Appearance:

Form: paste Grey Colour: Odour: Ester-like

(Contd. on page 4)



Safety data sheet according to 1907/2006/EC, Article 31 / ISO 11014

Printing date 28.11.2012 Version number 6 Revision: 28.11.2012

Trade name: Hilti HIT-HY20

		(Contd. of page 3)
· Odour threshold:	Not determined	
· pH-value:	Component A: not applicable Component B: ~ 6	
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Not determined Not determined	
· Flash point:	Component A: > 100 °C (DIN 53213) Component B: not applicable	
· Inflammability (solid, gaseous)	Not determined	
· Ignition temperature:	Not determined	
· Decomposition temperature:	Component B: SADT 65°C UN test H4	
· Self-inflammability:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive.	
· Critical values for explosion: Lower: Upper:	Not determined Not determined	
· Vapour pressure:	Component A: < 0.1 hPa (20 °C)	
 Density at 20°C Relative density Vapour density Evaporation rate 	1.1 g/cm3 (DIN 51757) Not determined Not determined Not determined	
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix	
· Partition coefficient (n-octanol/wat	er): Not determined	
· Viscosity: dynamic at 23°C: kinematic at 20°C:	~ 90 Pa.s (DIN 53788) > 20 s (DIN 53211/4)	
· Solvent content: Organic solvents: Water: · Other information	0 % Component B: ~ 30% No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- $\cdot \ \textbf{Incompatible materials:} \ No \ further \ relevant \ information \ available.$
- $\cdot \ \textbf{Hazardous decomposition products:} \ \ \textbf{No dangerous decomposition products known}$

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: No irritant effect.
- \cdot **Sensitization:** Sensitization possible by skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- \cdot Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects: Not determined

(Contd. on page 5)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.11.2012 Version number 6 Revision: 28.11.2012

/ ISO 11014

Trade name: Hilti HIT-HY20

(Contd. of page 4) • Additional ecological information:

- · According to recipe contains the following heavy metals and compounds according to EC guideline NO. 76/464 EC: None
- General notes: The product does not contain organically bounded halogens (AOX-free).
 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- $\cdot \ Waste \ treatment \ methods$
- $\cdot \ Recommendation$

For disposal, local regulations issued by the authorities must be observed.

Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations.

After curing, the product can be disposed of with household waste.

After curii	After curing, the product can be disposed of with nousehold waste.		
· European	· European waste catalogue		
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS,		
	VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS		
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)		
08 04 09*	waste adhesives and sealants containing organic solvents or other dangerous substances		
20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL		
	WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS		
20 01 00	separately collected fractions (except 15 01)		
20 01 27*	paint, inks, adhesives and resins containing dangerous substances		

- · Uncleaned packagings:
- · Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Disposal must be made according to official regulations.

Empty packs: May be disposed via the local Green Dot collecting system (Repak) or EAK waste material code 150102 (plastic packaging materials)

Transport information	
UN-Number ADR, ADN, IMDG, IATA	Void
UN proper shipping name ADR, ADN, IMDG, IATA	Void
Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
Packing group ADR, IMDG, IATA	Void
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MA the IBC Code	RPOL73/78 and Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications. available oxygen content $<1\ \%$
HS-Code:	3214 10 10: Glaziers' putty, grafting putty, resin cements, caulking compounds and other mastics

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations

Council Directive 89/391/EEC of 12 June 1989 on the introduction of measures to encourage improvements in the safety and health of workers at work. Article 12 Training of workers

- $\cdot \textbf{Information about limitation of use:} \ Employment \ restrictions \ concerning \ young \ persons \ must \ be \ observed.$
- $\cdot \ Other \ regulations, limitations \ and \ prohibitive \ regulations$
- · Substances of very high concern (SVHC) according to REACH, Article 57 None

(Contd. on page 6)



Safety data sheet ccording to 1907/2006/EC, Article 31 / ISO 11014

Printing date 28.11.2012 Version number 6 Revision: 28.11.2012

Trade name: Hilti HIT-HY20

 \cdot Chemical safety assessment: not required.

(Contd. of page 5)

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H241 Heating may cause a fire or explosion.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

R3 Extreme risk of explosion by shock, friction, fire or other sources of ignition.

R36 Irritating to eyes.

R43 May cause sensitisation by skin contact.

R7 May cause fire.

$\cdot \ \textbf{Department issuing data specification sheet:}$

Hilti Entwicklungsgesellschaft mbH

Hiltistrasse 6 D-86916 Kaufering Tel.: +49 8191 906310

Fax: +49 8191 90176310 e-mail: anchor.hse@hilti.com • Contact: Mechthild Krauter

 \cdot * Data compared to the previous version altered.

Œ