

A4 316 Equivalent Corrosion Resistance

$< 1\text{mm}$
 $\frac{1}{25}''$
 $\geq 6\text{mm}$
 $\frac{1}{4}''$
 $< 1\text{mm}$
 $\frac{1}{25}''$

S-BT-GR M8/7 SN 6 HL

	SBT 6
	TS-BT 5.3-95 S
	S-SH BT M8
	Torque Tool S-BT 1/4" 16 Nm / 11.8 lb-ft
	S-NS 13 C 95/3 1/4"
	S-IC BT

1

SBT 6

2

> 200 N
> 45 lb

3

4

RPM 2000
200

5

2

6

7

click

SBT 6

8

1 2

9

10

1 2 3

11

12

S-IC BT

12

1x 2x

13

1.6-7mm
1/16 - 9/32"

$\geq 13\text{mm}$
1/2"

14a

16Nm
11.8 ft-lb

1 2 3 click

14b

SBT 6

14c

$\leq 16\text{Nm}$
11.8 ft-lb

X-FCM-F/R
X-FCM-F/R NG
X-FCM-F/R HL

CE

23
Hilti Corporation,
Feldkircherstrasse 100,
LI-9494 Schaan
Hilti-SF-DoP-044
ETA-23/0001
EAD 333037-00-0602
0672-CPR
Threaded studs for connection
of materials to structural steel
and aluminium members
www.hilti.group